



Cinema Curved is a new born in the family of fixed installation screens.
 This new product, designed for wide open spaces and spectacular projections, engages the viewer with high-quality images and an exciting, high-impact cinema experience.
 The fabric-anchoring system has been designed to make assembly operations quicker and simpler.
 The alluminium frame is completely surrounded from the screen fabric, which is fastened directly to the frame structure through a new anchoring system.
 Surface is always welded on the vertical side
 Cinema Curved screens are produced in sizes from 7m to 24m.

See page **87**
 for Technical data



▲ Elastic stretchers and eyelet detail

Create your own screen with the PSS

> **Personalized dimensions:** width and height

Projection Surfaces (see page 6)

- > ReferenceWhite / ReferenceGrey
- > VisionWhite / VisionWhitePro
- > ViisonAcoustik / VisionMacroAcoustik

Standard Accessories

- > Iron junction and corners
- > Brackets for wall mount
- > Brackets for stiffener
- > M8 screws set
- > Elastics Stretcher
- > Fabric angles (for precise finishing)

Surfaces Fireproof Certifications




PSS Formats


1.78:1	1.89:1	2.35:1	2.37:1	2.40:1
16:9		21:9		

Cinema Curved



Aspect Ratio	Viewing Width	Viewing Height	Diagonal Inches	Overall Width	Overall Height	Total Depth	Surface/Wall Distance	Radius of Curvature
	A	B	N	A	B	F	J	R
1,78 (16:9)	7000	3933	316	7000	3933	350	180	36047
	8000	4494	361	8000	4494	350	155	41197
	9000	5056	406	9000	5056	400	181	46346
	10000	5618	452	10000	5618	400	157	51496
	11000	6180	497	11000	6180	450	182	56646
	12000	6742	542	12000	6742	450	158	61795
	13000	7303	587	13000	7303	500	184	66945
	14000	7865	632	14000	7865	500	159	72094
	15000	8427	677	15000	8427	550	185	77244
	16000	8989	723	16000	8989	550	161	82394
17000	9551	768	17000	9551	600	186	87543	



2,35 (21:9)	7000	2979	300	7000	2979	350	180	36047
	8000	3404	342	8000	3404	350	155	41197
	9000	3830	385	9000	3830	400	181	46346
	10000	4255	428	10000	4255	400	157	51496
	11000	4681	471	11000	4681	450	182	56646
	12000	5106	513	12000	5106	450	158	61795
	13000	5532	556	13000	5532	500	184	66945
	14000	5957	599	14000	5957	500	159	72094
	15000	6383	642	15000	6383	550	185	77244
	16000	6809	685	16000	6809	550	161	82394
	17000	7234	727	17000	7234	600	186	87543
	18000	7660	770	18000	7660	600	162	92693
	19000	8085	813	19000	8085	650	188	97842
	20000	8511	856	20000	8511	700	213	102992
21000	8936	899	21000	8936	750	239	108142	
22000	9362	941	22000	9362	800	265	113291	
23000	9787	984	23000	9787	800	240	118441	



2,40	7000	2917	299	7000	2917	350	180	36047
	8000	3333	341	8000	3333	350	155	41197
	9000	3750	384	9000	3750	400	181	46346
	10000	4167	427	10000	4167	400	157	51496
	11000	4583	469	11000	4583	450	182	56646
	12000	5000	512	12000	5000	450	158	61795
	13000	5417	554	13000	5417	500	184	66945
	14000	5833	597	14000	5833	500	159	72094
	15000	6250	640	15000	6250	550	185	77244
	16000	6667	682	16000	6667	550	161	82394
	17000	7083	725	17000	7083	600	186	87543
	18000	7500	768	18000	7500	600	162	92693
	19000	7917	810	19000	7917	650	188	97842
	20000	8333	853	20000	8333	700	213	102992
21000	8750	896	21000	8750	750	239	108142	
22000	9167	938	22000	9167	800	265	113291	
23000	9583	981	23000	9583	800	240	118441	
24000	10000	1024	24000	10000	850	266	123590	



Viewing distances, flat and curved, weights are available upon request.